

SEM10-F Boehringer B2T

Replacement 10,4" Boehringer



Overview

- 10,4" TFT monitor for Boehringer B2T
- Screen diagonal 10,4"
- Connector and signal timing compatible to the control
- Interface 9pin special D-SUB plug, cable 1:1 male/female 9pin
- Fast and simple exchange without any specialized knowledge

Description

The monitors SEM10-F are used as replacement for 12" CRT-monitors monochrome for the control Philips B2T from Boehringer.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu.

For mounting in panels with protection glass in the section of the 12" CRT without any mechanical changes.

Fast and simple replacement without any specialized knowledge.

Technical data

Overview:

Industrial TFT monitor 10" for mounting in panels with protection glass

Control:

Philips B2T

Original monitor:

14" CRT-monitor

Interfaces

D-Sub 9 plug, special

Synchronisation / Timings:

compatible to the control

Resolution:

max. 1024x768

Visible picture:

211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 500 cd/qm, 1000:1

Power supply:

90-260 VAC IEC plug with fuse

Mechanical dimension:

Case: 260 x 190 x 95 mm

Frontpanel: 290 x 228 mm

mounting holes: 272 x 190 mm

Material:

Frontpanel: aluminium powder-coated black, without Protective glass

Case: aluminium

Environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms:

En55022 EN55024 EN61010-1

Part number

10030717 SEM10-F-Boehringer B2T