

SEM10-F Delem DA24

TFT-monitor 10,4" frontpanel



Overview

- TFT / LCD monitor for Delem DA24
- screen diagonal 10,4"
- Connector 10-pin Edgeconnector
- Input frequencies from 15 kHz / 50Hz
- long-term availability
- Frontpanel for mounting holes for the old CRT-chassis/ tube
- different colors available

• Description

Monitors SEM10-F are used as replacement for 12" CRT-monitors monochrome in machines of Delem with control DA24.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Frontpanel with mounting holes to fix the monitor in the crt-chassis of the tube, this means fast and simple replacement with no specialized knowledge.

Technical data

Overview:

Industrial TFT monitor 10,4" for mounting in controlpanel with existing protective glass

control:

Delem DA24

Interfaces:

10-pin Edgeconnector

Synchronisation / Timings:

compatible to control

Resolution:

max. 800x600

Visible picture:

211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power supply:

12 VDC via signal line

MTBF:

Backlights min. 50000h

Mechanical dimension:

Case: 260 x 190 x 55 (95)mm

Frontpanel: 290 x 228mm

Mounting holes: 272 x 190 mm

Material:

Frontpanel: aluminium powder coated black without Protective glass,

Case: aluminium

environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms

EN55022 EN55024 EN61010-1

Part number:

10030737 SEM10-F Delem DA24 CRT