

SEM10-F Delem DA58

TFT-monitor 10,4"



Overview

- TFT / LCD monitor for Delem DA58
- screen diagonal 10,4"
- Interface 10-pin connector
- connector and signal timing compatible to the control
- 2-frontpanel system for easy mounting in existing monitor section of 12" CRT
- the exchange is fast and simple and without any specialized knowledge

Description

The monitors SEM10-F are used as replacement for 12" CRT-monitors on control DA58 from Delem.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu.

The mounting has to be made in the section of the 12" CRT without any mechanical changes. Fast and simple replacement without any specialized knowledge.

Technical Data

Overview:

Industrial TFT monitor 10,4" for Delem

Control:

Delem DA-58

Original monitor:

26S12MA001, 26C12001, 26C12MA001

Synchronisation / Timings:

compatible

Resolution:

max. 1024x768

Visible picture:

211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 500 cd/qm, 1000:1

Power supply:

90-260VAC, optional 24VDC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

Case: 260 x 190 x 55 (95)mm

Frontpanel: 267 x 197 x 3mm

Section operator panel: min. 256 x 186mm

Material:

Frontpanel: Aluminium powder-coated black .

Integrated protection glass

Case: Aluminium

Environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norm:

En55022 EN55024 EN61010-1

Part Number:

10030932 SEM10-F-Delem-DA58

10050502 Option 24VDC Power supply