

# SEM10-F Delem DA65

## TFT-monitor 10,4"



### Overview

- TFT / LCD Monitor for Delem DA65
- replacement for 26S12MA001, 26C12001, 26C12MA001
- Interfaces HD-SUB15
- connector and signal timing compatible to the control
- 2-frontpanel system for easy mounting in existing monitor section of 12" CRT
- the exchange is fast and simple and without any specialized knowledge

### Description

The monitors SEM10-F are used as replacement for 12" CRT-monitors in control DA65 from Delem.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The mounting has to be made in the section of the 12" CRT without any mechanical changes. Fast and simple replacement without any specialized knowledge. The representation is in the gray scale of the system.

### Technical Data

#### **Overview**

Industrial TFT monitor 10,4" for Delem

#### **Control:**

DA-65

#### **Original monitor:**

26S12MA001, 26C12001, 26C12MA001

#### **Synchronisation / Timings:**

compatible

#### **Resolution:**

max. 1024x768

#### **Adjustments:**

via on-screen-menu

#### **Brightness / Contrast:**

min. 500 cd/qm, 1000:1

#### **Power supply:**

12VDC via screwclamps

#### **MTBF:**

Backlights min. 50000h

#### **Mechanical dimension:**

Case: 260 x 190 x 55 (95)mm

Frontplate: 267 x 197 x 3mm

cutout operator panel: min. 256 x 186mm

#### **Material:**

Frontpanel: Aluminium powder-coated,

Protecting class

Case: Aluminium

#### **Environmental conditions:**

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

#### **Protection class:**

Front IP 65

#### **Norms**

En55022 EN55024 EN61010-1

### Part Number:

10030933      SEM10-F-Delem-DA65