

SEM10-F Delem DA69

TFT-monitor 10,4"



Overview

- TFT / LCD Monitor for Delem DA69
- screen diagonal 10,4"
- Interfaces HD-SUB15
- connector and signal timing compatible to the control
- 2-frontpanel system for easy mounting in existing monitor section of 12" CRT
- the exchange is fast and simple and without any specialized knowledge

Description

The monitors SEM10-F are used as replacement for 12" CRT-monitors in control DA69 from Delem.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The mounting has to be made in the section of the 12" CRT without any mechanical changes. Fast and simple replacement without any specialized knowledge. The representation is in the gray scale of the system.

Technical Data

Overview

Industrial TFT monitor 10,4" for Delem

Control:

DA-69

Original monitor:

26S12MA001, 26C12001, 26C12MA001

Synchronisation / Timings:

compatible

Resolution:

max. 1024x768

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 500 cd/qm, 1000:1

Power supply:

90-260 VAC

MTBF:

Backlights min. 50000h

Mechanical dimension:

Case: 260 x 190 x 55 (95)mm

Frontplate: 267 x 197 x 3mm

cutout operator panel: min. 256 x 186mm

Material:

Frontpanel: Aluminium powder-coated black,

Protecting class

Case: Aluminium

Environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms

En55022 EN55024 EN61010-1

Part Number:

10030934 SEM10-F-Delem-DA69