

SEM6-O Delem DA21+21e

TFT-monitor 6,4" openframe modul



Overview

- 6,4" TFT / LCD Monitor for special frequencies
- replacement for 7" CRT monochrome
- interface compatible to control
- long term availability
- customized adjustment possible
- adapter for easy mounting in existing frontpanel

• Description

Monitors SEM6-O are used as replacement for CRT-monitors in Delem machines with control DA21 and DA21e.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. The monitors are mounting via mounting brackets on the threaded bolts in the existing frontpanel.

Technical data

Overview:

Industrial TFT monitor 6,4" for mounting in controlpanel

control:

DA21 and DA21e

monitor:

7" CRT monochrome

Interfaces:

edgeconnector 10-pins

Synchronisation / Timings:

compatible to control

Resolution:

max. 640x480

Visible picture:

134 x101mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 300 cd/qm, 500:1

Power supply:

12 VDC via video line

MTBF:

Backlights min. 50000h

Material:Frontpanel: aluminium

environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Norms:

En55022 EN55024 EN61010-1

Part number

10030975 SEM6-O Openframe