SEM12-F Fanuc 15-16-18-20 TFT Replacement 12" Fanuc





Übersicht

- 12 " TFT / LCD Monitor for Fanuc
- Replacement for 14" CRT monitor "colour" A61L-0001-0074, A61L-0001-0094, A61L-0001-0096
- connector and signal timing compatible to the control
- · settings via on-screen-menu
- long-term availability
- frontpanel black with holes for mounting in CRT- chassis

Description:

The monitors SEM12-F are used as replacement for 14" CRT-monitors colour in Fanuc / GE Fanuc. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement with mounting holes in the frontpanel on the mounting points of the tube without any specialized knowledge.

Technical Data:

Overview:

Industrial TFT monitor 12" for Fanuc machine

Control:

Fanuc 6, 10, 11, 15, 15T, 15M, 15A, 15B, 16, 18, 20, 16T, 16M, 18M, 20T

Original monitor:

14" CRT- monitor colour A61L-0001-0074, A61L-0001-0094, A61L-0001-0096

Interfaces:

Blue Honda male 20-pol.

Synchronisation / Timings:

combatible

Resolution:

max. 800x600

Adjustments:

via OnScreen Menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power Suply

90-260 VAC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

combatible for mounting in crt-case/chassis

Material:

Frontpanel: Aluminium powder-coated black

Environmental conditions:

operation temperature 0-50°C storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms:

EN55022, EN55024, EN61010-1

Part Number:

10030980 SEM12-F-Fanuc