SEM10-O Mikron TFT-monitor 10,4"





Overview

- TFT / LCD monitor for Mikronl
- screen diagonal 10,4"
- Interfaces HD-SUB15 female
- mountings compatible
- replacement is easy
- long-term availability

Description

The monitors SEM10-O are used as Replacement in maschines of Heidenhain with control TNC430/TNC426. The connector and signal timing are compatible with the control. The monitor modul has to be screwed from behind on the existing panel, the mounting points are the same as the original monitor. Fast and simple replacement without any specialized knowledge possible.

Technical data

Overview:

Industrial TFT monitor 10,4" for Mikron

control:

Heidenhain TNC426/TNC 430

timings: compatible Resolution:

max. 800x600

Visible picture: 211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 300 cd/qm, 500:1

Power supply:

24VDC

Interfaces:

HD-SUB15 femalel

MTBF:

Backlights min. 40000h

Mechanical dimensions:

Case:300 x 220 x 55 mm

Material:

Case: aluminium

Environmental conditions:

Operation temperature 0-50°C Storage temperature 0-65°C

Humidity: 10 - 80 % rel. Humidity, not condensing

Norms:

En55022 EN55024 EN61010-1

Part number

10030862 SEM10-O-Mikron