

SEM12-F Unipro 80

TFT-Replacement 12"



Overview

- 12 " TFT / LCD Monitor for Heller with control Unipro 80
- Replacement for 12" CRT monochrome for panels with integrated protection glass
- e.g. 2MCS1219, 2MM912XCTN00, 2MK112XCTN04, 2MK112XCTN07
- connector and signal timing compatible to the control
- settings via on-screen-menu
- frontpanel black with mounting holes

Description

The monitors SEM12-F are used as Replacement for 12" CRT-monitors in control Unipro 80 from Heller.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. Fast and simple replacement through mounting holes on the back of the operator panel. Therefore it is necessary to drill 4 holes in the Operator panel.

Technical Data

Overview:

Industrial TFT Monitor 12" for mounting in operator panel with integrated protection glass

Control:

Unipro 80

Original monitor:

12" CRT-monitor monochrome
2MSC1219, 2MM912XCTN00
2MK112XCTN04, 2MK112XCTN07

Interfaces:

16-pin flatcable

Synchronisation / Timings:

compatible

Resolution:

max. 800x600

Visible Picture:

246x185mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power supply:

90-260VAC via screw clamps

MTBF:

Backlights min. 50000h

Mechanical dimensions:

case: 307x225x65mm
frontpanel 330x260x3 mm
mounting holes: 310x240mm

Material:

Frontpanel: aluminium powder-coated black

Environmental conditions:

Operating temperature 0-50°C
Storage temperature 0-65°C
Humidity: 10 - 80 % rel. humidity, not condensing

Norms:

EN55022 EN55024 EN61010-1

Part number

10030865 SEM12-F-Heller-Unipro 80