

SEM12-F Mazak M2, T2, T+ TFT Replacement 12"



interfaces



Overview

- 12 " TFT / LCD monitor for Mazak with Mazatrol M2, T2, T+
- replacement for 14" crt-monitor "color" in control panel with integrated protection glass
- connector and timing compatible
- Settings via on-screen-menu
- long-term availability
- Frontpanel black with holes for mounting in CRT chassis

Description:

The monitors SEM12-F are used as replacement for 14" CRT-monitors in Mazak cnc-lathe with control Mazatrol M2, T2, T+ . The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement through mounting holes in the crt-chassis on the mounting points of the tube without any specialized knowledge.

Technical Data:

Overview:

Industrial TFT monitor 12" for Mazak machine

Control:

Mazatrol M2, T2, T+

Interfaces:

15-pin special plug

Synchronisation / Timings:
compatible

Resolution:
max. 800x600

Adjustments:
via OnScreen Menu

Brightness/Contrast
min. 400 cd/qm, 500:1

Power Supply:
100 VAC via 3-pin Molexplug

MTBF:

Backlights min. 50000h

Mechanical dimensions:

Case: 307 x 225 x 65mm

Frontpanel: 330 x 260 x 3mm

through-holes compatible for mounting in crt-case/
-chassis (310x240mm)

Material:

Frontpanel: Aluminium powder-coated black

Environmental conditions:

operating temperature: 0-50°C

storage temperature: 0-65°C

humidity: 10 - 80 % relative humidity, not
condensing

Norms

EN55022, EN55024, EN61010-1

Part Number:

10030939 SEM12-F- Mazak M2, T2, T+