

SEM12-F Mitsubishi FX 10/20

TFT-replacement 12"



Overview

- 12 " TFT / LCD monitor for Mitsubishi FX 10/20
- replacement for CDT14148B 14" crt-monitor in control panel with integrated protection glass
- connector and timing compatible
- Settings via on-screen-menu
- long-term availability
- Frontpanel black with holes for mounting in CRT chassis

Description:

The monitors SEM12-F are used as replacement for 14" CRT-monitor color s in Mitsubishi FX10/20 machine. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement through mounting holes in the crt-chassis on the mounting points of the tube without any specialized knowledge.

Technical Data:

Overview:

Industrial TFT monitor 12" for FX 10/20 machine

Control:

Mitsubishi

Interfaces:

HD-SUB 15

Synchronisation / Timings:

compatible

Resolution:

max. 800x600

Adjustments:

via OnScreen Menu

Brightness/Contrast

min. 400 cd/qm, 500:1

Power Suply:

90-260VAC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

Case: 307 x 225 x 65mm

Frontpanel: 330 x 260 x 3mm

mounting holes compatible for mounting in crt-case/ -chassis (310x240mm)

Material:

Frontpanel: Aluminium powder-coated black

Environmental conditions:

operating temperature: 0-50°C

storage temperature: 0-65°C

humidity: 10 - 80 % relative humidity, not condensing

Norms

EN55022, EN55024, EN61010-1

Part Number:

10030844 SEM12-F-Mitsubishi FX 10/20