

SEM10-K AVUS 3/4 - AS256

TFT-Replacement-monitor 10,4" Siemens



Overview

- 10,4 " TFT / LCD monitor for Siemens Avus-3, Avus-4 and AS256
- Replacement for 12" CRT-monitor monochrome
- Connector and signal timing compatible to the control
- Settings via on-screen-menu
- Front adapter made of plastic with original curve of the CRT

Description

The monitore SEM10-K are used as replacement for 12" CRT-monitors for the control Avus3, Avus4 and AS256 from Siemens.

The default timing is compatible to the control, this means after connecting the monitor, the visualisation works correctly. Further adjustments can be made via on-screen-menu.

The connector and interface for the graphic-signal are compatible to the control.

Replacementmonitor with milled frontadapter made of plastic with original curve of the CRT, so the replacement is easy. The monitor has to be mounted in the old CRT-chassis.

The curved front adapter guarantees a good sealing in the panel.

Technical data

Overview :

Industrie TFT Monitor 10,4" für rückseitigen Einbau in Bedienpanel oder Steuerpult, Befestigung am Chassis der Röhre

Control:

Siemens Avus-3, Avus-4 and AS256

Original monitor:

12" CRT monitor monochrome

Interfaces:

1 x BNC

Synchronisation / Timings:

compatible to the control

Resolution:

max. 800x600

Visible picture:

211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power supply:

115/230VAC, optional 12 or 24VDC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

compatible

Material:

Frontpanel: front adapter made of plastic with original curve of the CRT, Protective glass

environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms:

EN55022 EN55024 EN61010-1

Part number

SEM10-K-Siemens-Avus-AS256