

SEM10-F Traub TFT-replacement 10"



Overview

- 10 " TFT / LCD monitor for Traub with mitsubishi control TX8
- replacement for 12" crt-monitor "monochrome" in control panel with integrated protection glass
- connector and timing compatible
- Settings via on-screen-menu
- long-term availability
- Frontpanel black with holes for mounting in CRT chassis

Description:

The monitors SEM10-F are used as replacement for 12" CRT-monitors in Traub cnc-lathe with control TX8 from mitsubishi. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement through mounting holes in the crt-chassis on the mounting points of the tube without any specialized knowledge.

Technical Data:

Overview:

Industry TFT monitor 10" for Traub machine

Control:

Mitsubishi TX8

Interfaces:

15-pole special plug

Synchronisation / Timings:

compatible

Resolution:

max. 800x600

Adjustments:

via OnScreen Menu

Brightness/Contrast

min. 400 cd/qm, 500:1

Power Supply:

connector cable 100 VAC via 3-pin Molexplug

MTBF:

Backlights min. 50000h

Mechanical dimensions:

Case: 260 x 190 x 55mm

Frontpanel: 290 x 228 x 3mm

mounting holes compatible for mounting in crt-case/ -chassis (272x190mm)

Material:

Frontpanel: Aluminium powder-coated black

Environmental conditions::

operating temperature: 0-50°C

storage temperature: 0-65°C

humidity: 10 - 80 % relative humidity, not condensing

Norms

EN55022, EN55024, EN61010-1

Part Number:

10030811 SEM10-F-Traub